

OTG-200

by OKAYO-Taiwan

- ⦿ 42 channels with talk-back function
- ⦿ automatic channel setting
- ⦿ programmable display
- ⦿ 3 different guidance settings



The OTG-200 is an interactive guidance system with 3 different settings available. Whether you use it for conventional group tours, podium discussions or seminars: the OTG-200 is always the ideal choice.

42 transmission channels enable parallel group guides, while an automatic channel lock prevents visitors from leaving the group by mistake. If participants move too far away from the group, the device alerts them with an audible signal.

Three different guide settings make this model incredibly versatile. Actively integrate your visitors into the action using the talk-back function, which allows their receiver to communicate with the group leader as well as the other visitors.

The illuminated LCD screen displays the choice of frequency range, channels and battery status.

With a range of up to 100 metres, the OTG-200 system can be used both indoors and outdoors.

OTG-200

Frequencies

The OTG-200 group guidance system has a range of up to 100 m. Channels can be set manually, via the charging station or by the group leader with the touch of a button. The number of group participants can be displayed on the transmitter's screen. Up to 42 channels (823-832/863-865 Mhz) are available. The names of the channels can be customised as required.

Storage

Space-saving and handy: the case is not only a stylish way to transport the devices, but it is also practical with space for up to 25 charging bays holding the transmitter and receivers. The orderly way to charge and store: the 19" charging unit offers space for up to 50 devices.

Application fields

- tours, training sessions, podium discussions
- up to 2 transmitters operating in parallel possible per tour
- multiple transmitters can be used for discussions
- talk-back function for participants
- Transmitter can be used with microphone PM-20A as a hand-held mic



CHG-25 19" charging unit with 25 bays



19" charging unit C-50 with 50 bays

Technical information

Dimensions:	Depth 3,2 cm Width 4,6 cm Height 9,5 cm (without antenna)
Weight:	105g (transmitter) 105g (receiver) weight incl. battery
Operating temp.:	-10° to +50° C
Screen:	Illuminated digital LCD display
Microphone:	3.5 mm stereo jack for external microphone
Headphone jack:	3.5 mm stereo jack
Operating range:	up to 100 m
Battery:	1.2 V 2000mAh Ni-MH battery or 1.5 V alkaline battery
Fastening:	Belt clip and carry strap
Operating time:	16-18 hours
Charging period:	approx. 4-6 hours
Certificates:	CE-certified and checked by TÜV Rheinland for compliance with ISO 9001-2000. R&TTE permits its use in all EU nations FCC, RoHS
Guarantee period:	24 months guarantee

Charging stations

CHG-25 Ladestation
charging station case (for 25 devices) with removable cover

Dimensions: Width 44,4 cm
Depth 29,0 cm
Height 15,9 cm
Wight: 6 kg

C50 Ladestation
19" charging station unit (for 50 devices)

Dimensions: Width 48,2 cm
Depth 24,3 cm
Height 39,9 cm
Wight: 16 kg

soundgarden is an authorised retailer and service provider for the OKAYO system.

More information:

soundgarden audioguidance GmbH
Brabanter Straße 4
80805 Munich | Germany
Tel.: +49 (0) 89 317708-52
www.audioguide.de | info@audioguide.de

Accessories



EM-305



HM-54A



EM-101



LM-94A



EM-201



EMC-300



PM-24A



EMC-205